





Process for measuring the nitrate content of drinking water uses a wavelength inducing an absorption maximum and an absorption minimum of the nitrate concentration curve

Veröffentlichungsnr. (Sek.)

DE19902396

Veröffentlichungsdatum:

2000-08-17

Erfinder:

MUELLER KIRSTEN (DE); STEUERWALD RALF (DE)

Anmelder:

STAIGER MOHILO & CO GMBH (DE)

Veröffentlichungsnummer:

☐ DE19902396

Aktenzeichen:

(EPIDOS-INPADOC-normiert)

DE19991002396 19990122

Prioritätsaktenzeichen:

(EPIDOS-INPADOC-normiert)

DE19991002396 19990122

Klassifikationssymbol (IPC):

G01N21/33; C02F1/70; C02F1/32; G01N33/18

Klassifikationssymbol (EC):

G01N21/33

Korrespondierende Patentschriften

Bibliographische Daten

Process for measuring the nitrate content of liquids uses a wavelength inducing one of the regions of absorption maximum and one the regions of the absorption minimum of the nitrate concentration curve. An Independent claim is also included for a device for carrying out the measuring process comprising a line having a transparent section realized by two measuring strips (10, 11) arranged next to each other in the front side of the head (32) of a measuring probe and limited by quartz glass windows (13, 14, 13', 14'). The measuring strips are formed as indentations of different widths connected to a UV source (15) whose light is divided onto two measuring branches (19, 20) each with a light path for receiving UV- and IR-beams via two deviating mirrors (17, 18) arranged across from one another.

Daten aus der esp@cenet Datenbank - - I2